



SUPER LIFE® 9000N 0W-20 STJLR.51.5122 Spec. **BENEFICIENT FULL SYNTHETIC MOTOR OIL**

SUPER LIFE® 9000N 0W-20 STJLR.51.5122 Spec. is manufactured with PAO Synthetic base stocks and the most advanced additive technology to meet the latest ILSAC GF-5 and API SN industry requirements as well as the performance demands of the latest emerging diesel and gasoline powered European engines where required SAE 0W-20 viscosity grade. It provides extraordinary engine protection under all severe driving conditions, including heavy load and stop- and -go conditions, rapid acceleration, sudden stops and high revving all push the engine to work harder, run hotter and high and low-temperature engine operation.

It is compatible with latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's) and meets the OEMs requirements for CO2 emissions reductions.



APPLICATIONS:

SUPER LIFE® 9000N 0W-20 STJLR.51.5122 Spec is specifically designed for Jaguar Land Rover engines requiring a lubricant with the STJLR.51.5122 specification and meets the following specifications:

SAE Viscosity Grade	0W-20
API SN/SM/SL	X
ILSAC GF-5	X
GM dexos1	X
GM 6094M	X
ACEA A1/B1	X
ACEA C5	X
MB 229.71	X
VW 508.00	X
VW 509.00	X
Porsche C20	X
Ford WSS-M2C925-A	X
Ford WSS-M2C947-A	X
Chrysler MS-6395	X
Honda/Acura HTO-06	X

BENEFITS:

- Ultimate engine protection. Increase thermal and oxidation stability at extreme high temperatures.
- Faster cold start and improve oil flow at extreme low temperature.
- Sustains maximum performance even when under high pressure.
- Synthetic base for added oxidation stability, improved volatility and low temperature properties.

- Protect against rust and corrosion caused by severe low temperature stop- and -go driving.
- Protect against harmful deposits and acid.
- Minimizes lubricant hydrodynamic friction, Fuel efficiency.
- Extend engine life
- Excellent at maintaining engine cleanliness.

TYPICAL CHARACTERISTICS

Test	Method	Typical Results
SAE Viscosity Grade	SAE J300	0W-20
API Gravity	ASTM D 287	36.95
Specific Gravity @ 15.6 °C (60°F)	ASTM D 1298	0.840
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D 445	40.1 8.0
Viscosity Index	ASTM D 2270	178
Flash Point, °C (°F)	ASTM D 92	225(437)
Pour Point, °C (°F)	ASTM D 97	-52(-61.6)
Low temperature(°C) Cranking Viscosity, cP	ASTMD 5293	5827@-35 °C
HTHS Viscosity @150°C, cP	ASTM D 4683	2.65
Noack, wt%	ASTM D 5800	6.60

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference MSDS Number 12022 database on our website at www.amtecol.com

