



SUPER LIFE® 6500-4T MCO **PREMIUM 4 - STROKE MOTORCYCLE OILS**

SUPER LIFE® 6500-4T MCO Products are designed to ensure good protection for the engine, wet clutch and gearbox used by all 4-stroke motorbikes. They are formulated with an unique additive package chosen for exceptional wear protection, sludge and varnish resistance, and thermal stability.

APPLICATIONS:

SUPER LIFE® 6500-4T MCO Products are recommended for all types of 4-stroke motorcycles of manufacturers including HARLEY-DAVIDSON, HONDA, SUZUKI, YAMAHA, KAWASAKI, SYM etc.

API SL
JASO MA 2

BENEFITS:

- Help engine reach maximum performance and power, quickly starting up .
- Anti-wear properties, lower corrosion and friction. Give excellent protection for transmissions and wet clutches .
- Help reduce foaming and air-entrainment in high speed engines.
- Help engine running smoothly and freshly.
- Excellent fuel saving, lengthen the oil changing intervals, economize everything .
Prolongation of engine life .



TYPICAL CHARACTERISTICS

Test	Method	Typical Results		
		10W-30	10W-40	20W-50
SAE Viscosity grade	SAE J300	10W-30	10W-40	20W-50
API Gravity	ASTM D287	30.58	30.21	29.29
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.873	0.875	0.88
Viscosity @ 40°C cSt	ASTM D445	72.1	108	170
@ 100°C cSt		11.4	15.6	20.5
Viscosity Index	ASTM D2270	152	153	141
Flash Point, °C (°F)	ASTM D92	200(392)	200(392)	200(392)
Pour Point, °C (°F)	ASTM D97	-34(-30)	-34(-30)	-30(-22)
Total Base Number, mgKOH/g	ASTM D2896	7.0	7.0	7.0

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

*Reference SDS Number 12021 database on our website at www.amtecol.com
OR scan the code for a direct link*

