



SUPER LIFE® 6500M-4T MCO **SUPREME 4-STROKE MOTORCYCLE OILS**

SUPER LIFE® 6500M-4T MCO Products are supreme quality lubricants specially designed to ensure good protection for the engine, wet clutch and gearbox used by all 4-stroke motorbikes . They are formulated with a unique additive package chosen for exceptional wear protection, sludge and varnish resistance, and thermal stability. The slippage of the clutch system is minimized by the increased friction between the clutch plates, this then enables the power output to be increased at the rear tire. Improve power output and more reliability at the same time.

APPLICATIONS:

SUPER LIFE® 6500M-4T MCO Products are recommended for all types of 4-stroke motorcycles of manufacturers including HARLEY-DAVIDSON, HONDA, SUZUKI, YAMAHA, KAWASAKI, SYM , etc.

API SM
JASO MA 2

BENEFITS:

- Help engine reach maximum performance and power, quick starting up .
- Protect well heavy loaded parts in very severe conditions of operating : high speed, high temperature, rough roads .
- Anti-wear properties, lower corrosion and friction. Provide excellent protection for transmissions and wet clutches.
- Help reduce foaming and air-entrainment in high speed engines.
- Help engine running smoothly and freshly .
- Excellent fuel saving, lengthen the oil changing intervals, economize everything. Prolong engine life .
- Provide good characteristics in harmful deposit control to help keep the engine and gearbox running cleaner and provides good gearbox protection for incorporated gearboxes.

TYPICAL CHARACTERISTICS

Test	Method	Typical Results		
SAE Viscosity grade	SAE J300	10W-30	10W-40	20W-50
API Gravity	ASTM D287	31.14	31.14	29.66
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.87	0.87	0.878
Viscosity @ 40°C cSt @ 100°C cSt	ASTM D445	72.9 11.5	104 15.2	164 19.87
Viscosity Index	ASTM D2270	152	154	140
Flash Point, °C (°F)	ASTM D92	200(392)	200(392)	200(392)
Pour Point, °C (°F)	ASTM D97	-34(-30)	-34(-30)	-30(-22)
Total Base Number, mgKOH/g	ASTM D2896	7.5	7.5	7.5

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

*Reference SDS Number 12021 database on our website at www.amtecol.com
OR scan the code for a direct link*

