



SUPER LIFE® 5000-4T FS

FULL SYNTHETIC 4- STROKE MOTORCYCLE OILS

SUPER LIFE® 5000-4T FS Full synthetic four stroke motorcycle oils are designed specifically to provide unrivaled engine protection even in high temperature and high speed conditions. They meet the latest requirements of the first class motorcycle manufacturers in the world. They are blended from synthetic base oils with advanced additive packages to optimize the quality of motorcycle engines, increase engine power either operating under severe conditions or in very strict international motor racings.

APPLICATIONS:

SUPER LIFE® 5000-4T FS are recommended for all types of 4-stroke modern motorcycles of manufacturers including HARLEY-DAVIDSON, HONDA, SUZUKI, YAMAHA, KAWASAKI, SYM, etc.

API SJ/SH

JASO MA

BENEFITS:

- Help engine reach maximum performance and power, quickly starting up. Protect well heavy loaded parts in very severe conditions of operating : high speed, high temperature, rough roads . Help engine running smoothly and freshly .
- Anti-wear properties, lower corrosion and friction. Excellent fuel saving, lengthen the oil changing intervals, economize everything . Prolongation of engine life .
- Wet clutch protection
- Minimize foaming at high RPM
- Protect against piston scuffing
- Good detergent-dispersant properties to keep engine always clean .
- Excellent engine protection .

TYPICAL CHARACTERISTICS

Test	Method	Typical Results		
SAE Viscosity grade	SAE J300	10W-30	10W-40	10W-50
API Gravity	ASTM D287	34.00	33.42	31.52
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.855	0.858	0.868
Viscosity @ 40°C cSt @ 100°C cSt	ASTM D445	70.2 11.6	95 14.8	123 17.5
Viscosity Index	ASTM D2270	161	163	157
Flash Point, °C (°F)	ASTM D92	230(446)	230(446)	235(455)
Pour Point, °C (°F)	ASTM D97	-42(-43.6)	-42(-43.6)	-40(-40)
Total Base Number, mgKOH/g	ASTM D2896	7	7	7

*The above characteristics are average values based on recent production.
Minor variations which do not affect product performance are to be expected in normal manufacture.*

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

*Reference SDS Number 12022 database on our website at www.amtecol.com
OR scan the code for a direct link*

