



SUPER LIFE® 6500N-4T MCO **PREMIUM 4-STROKE MOTORCYCLE OILS**

SUPER LIFE® 6500N-4T MCO Products are superior performance premium quality lubricants specially designed to ensure maximum protection for all engine components, integral clutch (wet sump) and gearbox in severe operating extremes used by all modern 4-stroke motorbikes. They are formulated with a unique additive package chosen for exceptional wear protection, sludge and varnish resistance, and thermal stability. The slippage of the clutch system is minimized by the increased friction between the clutch plates, this then enables the power output to be increased at the rear tire. Improve power output and more reliability at the same time.

APPLICATIONS:

SUPER LIFE® 6500N-4T MCO Products are recommended for all types of 4-stroke motorcycles and ATVs of manufacturers including HARLEY-DAVIDSON, HONDA, SUZUKI, YAMAHA, KAWASAKI, SYM , etc. and high-powered motorcycles where API SN or JASO MA, MA2 oils are specified.

API SN
JASO MA, MA 2

BENEFITS:

- Optimal friction characteristics for maximum performance and power, quick starting up.
- Resist viscosity and thermal breakdown at high temperatures.
- Protect well heavy loaded parts in very severe conditions of operating : high speed, high temperature, rough roads .
- Anti-wear properties, lower corrosion and friction. Provide excellent protection for transmissions and wet clutches.
- Help reduce foaming and air-entrainment in high speed engines.
- Help engine running smoothly and freshly .
- Excellent fuel saving, lengthen the oil changing intervals, economize everything. Prolong engine life .
- Provide good characteristics in harmful deposit control to help keep the engine and gearbox running cleaner and provides good gearbox protection for incorporated gearboxes.

TYPICAL CHARACTERISTICS

SAE Viscosity grade	SAE J300	10W-30	10W-40	20W-50
API Gravity	ASTM D287	31.14	30.58	29.85
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.870	0.873	0.877
Viscosity @ 40°C cSt	ASTM D445	76.70	106.35	161.47
@ 100°C cSt		11.60	14.83	18.89
Viscosity Index	ASTM D2270	145	145	132

Flash Point, °C (°F)	ASTM D92	224(435)	224(435)	232(450)
Pour Point, °C (°F)	ASTM D97	-36(-33)	-36(-33)	-28(-18)
Low temperature (° C) Cranking Viscosity, cP	ASTM D5293	6420 @-25 ° C	6511 @-25 ° C	4853 @-15 ° C
Noack, wt%	ASTM D5800	7.50	10.45	8.42
Total Base Number, mgKOH/g	ASTM D2896	7.8	7.8	7.8

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

Reference SDS Number 12021 database on our website at www.amtecol.com

OR scan the code for a direct link

