



SUPER LIFE® 6500-4T SB SCO **PREMIUM SYNTHETIC BLEND 4 - STROKE** **SCOOTER OILS**

SUPER LIFE® 6500-4T SB SCO Products are designed to provide outstanding protection for the engine, transmission used by all 4-stroke modern Scooters . They are formulated with a mixture of high-tech synthetic and premium quality base stocks and the advanced additive technology for exceptional wear protection, sludge and varnish resistance, and thermal stability. High engine RPM and the operating temperatures of Scooter air-cooled or liquid-cooled engines fluctuate greatly, causing conventional lubricants to lose viscosity and reduce their ability to control wear, resulting in power loss and in shorter engine life. Formula 4-stroke synthetic blend Scooter oils with low friction additives help reduce power losses, resist shear and breakdown at elevated temperatures, maintaining their protective viscosity for excellent wear protection , minimizing friction for maximum power and extended engine life.

APPLICATIONS:

SUPER LIFE® 6500-4T SB SCO Products are recommended for all types of 4-stroke modern Scooters of European, Japanese, Taiwanese, Chinese, Indian manufacturers including VESPA, PIAGGIO, PEUGEOT, HONDA, SUZUKI, YAMAHA, KAWASAKI, APRILIA, BENELLI, SYM, KYMCO, TGB etc.

API SL
 JASO MB

BENEFITS:

- Help engine reach maximum performance and power, quickly starting up .
- Enhanced shear stability for engine running smoothly and freshly.
 Reduced vibration and engine noise.
- Excellent wear protection, lower corrosion. Longer bearing life.
- Help reduce foaming and air-entrainment in high speed engines.
- Excellent fuel saving, lengthen the oil changing intervals, economize everything .
 Prolongation of engine life .

TYPICAL CHARACTERISTICS

| Test | Method | Typical Results | | |
|--|------------|-----------------|--------------|-----------|
| | | 10W-30 | 10W-40 | 20W-50 |
| SAE Viscosity grade | SAE J300 | 10W-30 | 10W-40 | 20W-50 |
| API Gravity | ASTM D287 | 32.08 | 31.52 | 29.49 |
| Specific gravity @ 15.6°C (60°F) | ASTM D1298 | 0.865 | 0.868 | 0.879 |
| Viscosity @ 40°C cSt @ 100°C cSt | ASTM D445 | 73.3 11.6 | 103 15.20 | 160 20 |
| Viscosity Index | ASTM D2270 | 153 | 155 | 145 |
| Flash Point, °C (°F) | ASTM D92 | 205(401) | 205(401) | 210(410) |
| Pour Point, °C (°F) | ASTM D97 | -37(-35) | -37(-35) | -26(-15) |
| Total Base Number, mgKOH/g | ASTM D2896 | 7.0 | 7.0 | 7.0 |

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

*Reference SDS Number 12023 database on our website at www.amtecol.com
OR scan the code for a direct link*

