

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

DURALIFE® BRAKE CLEANER

Product Use: Brake Cleaner

Manufacturer :

AMTECOL, Inc.

810 Wright Ave, Richmond, CA 94804, U.S.A.

www.amtecol.com

Transportation Emergency & Emergency spill information :

Call CHEMTREC : (+1) 703-527-3887 (outside the U.S.), 1-800-424-9300 (in the U.S.)

Health Emergency : Amtecol Emergency Information Center : 1-866-268-1888

Other Product Information :

Technical Assistance/SDS info & Customer Service : 1-510-235-7979 Email : info@amtecol.com

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classification

Flammable Aerosol: Category 1. Acute Toxicity (oral): Category 4. Serious Eye Damage/Irritation: Category 2B. Skin Corrosion/Irritation: Category 2. Aspiration Hazard: Category 1. Reproductive Toxicity: Category 2. Carcinogenicity: Category 2. Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (central nervous system): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

Label Elements

Signal word : Danger



Hazard Statements

Extremely flammable aerosol.

Harmful if swallowed. Causes eye irritation. Causes skin irritation. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Suspected of causing cancer.

Causes damage to organs: cardiovascular system, sensory organs

Causes damage to organs through prolonged or repeated exposure: nervous system

May cause damage to organs through prolonged or repeated exposure: sensory organs

Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces.

Safety Data Sheet

No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area or open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Specific treatment (see Notes to Physician on this label). Get medical advice/attention if you feel unwell.

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary. This product contains methanol. Methanol poisoning can cause metabolic acidosis, blindness, and death. Onset of signs or symptoms may be delayed for 18 to 24 hours. If methanol poisoning is confirmed, intravenous (IV) administration of ethanol should be considered. Additional pharmacologic and supportive care should be based on the treating physician's judgement.

Hazards not otherwise classified

None.

15% of the mixture consists of ingredients of unknown acute oral toxicity.

15% of the mixture consists of ingredients of unknown acute dermal toxicity.

15% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3. COMPOSITION INFORMATION/ INGREDIENTS

COMPONENTS	CAS NUMBER	% WEIGHT
METHANOL	67-56-1	40 – 60
ACETONE	67-64-1	15 – 25
DIACETONE ALCOHOL	123-42-2	10 – 15
TOLUENE	108-88-3	0– 5
CARBON DIOXIDE	124 -38-9	5 - 15

SECTION 4. FIRST AID MEASURES

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact: Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed : May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed : Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information : IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.


SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media: Dry chemical, CO2, or water spray.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Contents under pressure. Exposure to high temperature may cause can to burst. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

NFPA 704 HAZARD RATINGS:



Safety Data Sheet

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions: In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

Reporting: Follow prescribed procedures for reporting and responding to larger releases. Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Safety Data Sheet

Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits

Component	ACGIH	OSHA-Z
Methanol 67-56-1	TWA: 200 ppm STEL: 250 ppm	TWA: 260 mg/m ³ (200ppm) PEL: 260 mg/m ³ (200ppm)
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm	TWA: 1800 mg/m ³ (750 ppm) PEL: 2400 mg/m ³ (1000 ppm)
Diacetone Alcohol 123-42-2	TWA: 50 ppm	TWA: 240 mg/m ³ (50 ppm)
Toluene 108-88-3	TWA: 50 ppm	TWA: 375 mg/m ³ (100 ppm)
Carbon Dioxide 124-38-9	TWA: 5000 ppm STEL: 30000 ppm	TWA: 18000 mg/m ³ (10000 ppm) PEL: 9000 mg/m ³ (5000 ppm)

Exposure controls

1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapors. For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear thin liquid	Freezing Point : No data available
Odor : Solvents hydrocarbons	Solubility : Poorly Soluble in water
Physical State : Liquid	Viscosity @ 100 °C : Not available
Evaporation Rate (nBuAc=1) : No data available	Vapor Pressure : No data available
Boiling Point : No data available	Vapor Density (air=1) : > = 1
Melting Point : No data available	pH : N/A
Specific Gravity : 0.80	Flammability (Explosive) Limits (% by volume in air) : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks. Contact with incompatible materials. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

Incompatible materials: Strong oxidizing agents. Strong acids. Strong bases.

Hazardous decomposition products: Hydrogen chloride. Trace amounts of chlorine and phosgene. Carbon oxides. Halogenated materials. Carbonyl halides.

SECTION 11. TOXICOLOGICAL INFORMATION

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness,

Safety Data Sheet

cracking, blistering, and pain. May cause target organ effects after skin contact.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Harmful if swallowed. Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

May cause blindness.

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Product Name	Route	Species	Value
Overall Product	Dermal	Rabbit	No data available; estimated 3,000-5,000 mg/kg
	Inhalation LC 50	Rat	No data available; estimated 20-50 mg/l (4hr)
	Oral LD 50	Rat	No data available; estimated 300-2,000 mg/l/kg
Methanol	Dermal LD 50	Rat	Estimated 1,000-2,000 mg/kg
	Inhalation LC 50	Rat	Estimated 10 -20 mg/l
Acetone	Inhalation LC 50	Mouse	44,000 mg/m3 (4hr)
	Oral LD 50	Mouse	3,000 mg/kg
Diacetone Alcohol	Dermal LD 50	Rabbit	13,630 mg/kg
	Oral LD 50	Rat	4,000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Overall Product	Species	Test Results
Aquatic		
Fish	Fish	LC 50 estimate 20 mg/l (96 hr)

Persistence and degradability: Not available.

Bioaccumulative potential: Not available.

Mobility in soil : No data available.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of waste from residues / unused products:

This material and its container must be disposed of as hazardous waste. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Dispose in a safe manner in accordance with local/national/international regulations.

Hazardous waste code:

F001: Waste Halogenated Solvent - Spent Halogenated Solvent Used in Degreasing F002: Waste Halogenated Solvent - Spent Halogenated Solvent

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

SECTION 14. TRANSPORT INFORMATION

1. In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1993, Flammable liquids

ICAO/IATA (air): UN1993, Flammable liquids

IMO/IMDG (water): Flammable liquids

Special Provisions: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test

Safety Data Sheet

pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or

less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

2. UN proper shipping name

Proper Shipping Name (DOT): Flammable liquids

Department of Transportation (DOT) Hazard Classes: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT): 3 - Flammable liquid

DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT): II - Medium Danger

DOT Special Provisions (49 CFR 172.102): B2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx): 150

DOT Packaging Non Bulk (49 CFR 173.xxx): 202

DOT Packaging Bulk (49 CFR 173.xxx): 242

3. Additional Information:

Other information: No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27): 5L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75): 60L

Safety Data Sheet

SECTION 15. REGULATORY INFORMATION

US federal regulations : This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Component	SARA 313	SARA 302	TPQ	RQ
Methanol Cas 67-56-1	Listed	Not listed	Not listed	Not listed
Acetone Cas 67-64-1	Not listed	Not listed	Not listed	Not listed
Diacetone Alcohol Cas123-42-2	Listed	Not listed	Not listed	Not listed
Toluene Case108-88-3	Listed	Not listed	Not listed	Not listed
Carbon Dioxide Cas 124-38-9	Not listed	Not listed	Not listed	Not listed

US OSHA HEALTH CLASSIFICATION: Hazardous per OSHA 29 CFR 1910.1200

SARA 311/312 Hazard Categories: Not Determined.

State Regulations:

Component	California Prop. 65 Cancer list	California - Prop 65 Developmental Toxicity	California Prop. 65 Reproductive Female	California Prop. 65 Reproductive Male	New Jersey Right-to-Know List:
Methanol Cas 67-56-1					Substance no. 0006 Substance no. 2422
Acetone Cas 67-64-1	Not listed	Not listed	Not listed	Not listed	Substance no. 2423 Substance no. 2425 Substance no. 2426
Diacetone Alcohol Cas123-42-2	Not listed	Not listed	Not listed	Not listed	Substance no. 2427 Substance no. 2428 Substance no. 2429
Toluene Case108-88-3	Not listed	Listed: January 1, 1991 Developmental toxin.	Not listed	Not listed	Substance no. 2430 Substance no. 1866 Substance no. 2422 Substance no. 2423 Substance no. 2425
Carbon Dioxide Cas 124-38-9	Not listed	Not listed	Not listed	Not listed	Substance no. 2426 Substance no. 2427 Substance no. 2428 Substance no. 2429 Substance no. 2430 Substance no. 2079 Substance no. 2422 Substance no. 2423 Substance no. 2425 Substance no. 2426 Substance no. 2427 Substance no. 2428 Substance no. 2429 Substance no. 2430 Substance no. 1222 Substance no. 0343

U.S. TSCA: The components of this product are listed on the TSCA Inventory.

Canadian Inventory:

The components of this product are listed on the Canadian DSL or NDSL Inventory.

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

SECTION 16. OTHER INFORMATION

HMIS RATINGS: Health: 2 Flammability: 3 Reactivity: 1 (0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

OSHA - Occupational Safety and Health Administration	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
ACGIH - American Conference of Government Industrial Hygienists	CAS - Chemical Abstract Service Number
GHS - Globally Harmonized System	SDS - Safety Data Sheet
API - American Petroleum Institute	IMO/IMDG - International Maritime Dangerous Goods Code
DOT - Department of Transportation (USA)	NCEL - New Chemical Exposure Limit
IARC - International Agency for Research on Cancer	NFPA - National Fire Protection Association (USA)
EPA - Environmental Protection Agency	SCBA - Self-Contained Breathing Apparatus
TLV - Threshold Limit Value	NTP - National Toxicology Program (USA)
HMIS -Hazardous Materials Identification	WHMIS -Workplace Hazardous Materials

Safety Data Sheet

System	Information System
NIOSH-National Institute for Occupational Safety and Health	TSCA-Toxic Substances Control Act
CASRN - Chemical Abstracts Service Registry Number	CERCLA - The Comprehensive Environmental Response, Compensation, and Liability Act
INSHT - National Institute for Health and Safety at Work	IOPC - International Oil Pollution Compensation
LEL - Lower Explosive Limit	NE - Not Established
SARA - Superfund Amendments and Reauthorization Act	UEL - Upper Explosive Limit

Prepared by : AMTECOL, Inc.
810 Wright Ave. , Richmond , CA 94804 , U.S.A.

Disclaimer of Warranty : The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.



AMTECOL RICHMOND FACILITY

AMERICAN HITECH PETROLEUM & CHEMICALS, INC.
810 WRIGHT AVE, RICHMOND CA 94804 USA
OFFICE TEL: 510-235-7979
FAX: 510-232-4846
EMAIL: INFO@AMTECOL.COM
WEBSITE: WWW.AMTECOL.COM