



DURALIFE® FLUSHING OIL

Duralife® Flushing oil is a high quality product designed specifically for flushing the internal surfaces of engines, hydraulic and other lubricating systems to remove varnish, carbon, grime, metallic particle sludge and other contaminants.

APPLICATIONS:

Duralife® Flushing oil is recommended for use in all engine types in passenger cars, 4WD's, light & heavy duty commercial vehicles, motorcycles, farming, mining, agricultural, industrial equipment, marine and stationary engines.

BENEFITS:

- Improves oil circulation.
- Cleans sticky piston rings and dissolves power-robbing deposits.
- Removes deposits and sludge for improved efficiency, fuel economy, lower emissions and minimizes compression loss (deposits in engines can accelerate wear by the time, causing power loss and increased fuel consumption).
- Optimal engine performance.

TECHNICAL DATA:

Specific Gravity @ 15.6°C (60°F)	0.868
Flash Point, °F (°C)	212 (100)
Pour Point, °F (°C)	5 (-15)
Viscosity @ 40 °C, cSt	22.0

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

DIRECTIONS FOR USE:

- Drain engine oil when engine is warm, by removing the sump plug.
- Replace the sum plug then fill **Duralife® Flushing oil** to the normal sump capacity.
- Start the engine and idle at low revolutions for 10 minutes with occasional bursts at higher revolutions.
- Stop the engine, remove the sum plug and thoroughly drain flushing oil. If it appears very dirty, it is advisable to repeat the process with new **Duralife® Flushing oil**.
- Renew the oil filter or clean external oil filter, whichever is applicable.
- Refill with the correct grade of engine oil.

WARNING: Keep out of reach of children and avoid contact with eyes. Do not discharge used liquid into drains.

Reference SDS Number 12052 database on our website at www.amtecol.com OR scan the code for a direct link

