



## SUPER LIFE 3500D-2T FS

### SUPREME FULL SYNTHETIC LOW SMOKE 2-CYCLE POWER EQUIPMENT OIL *with* FUEL STABILIZER

***SUPER LIFE 3500D-2T FS*** is a supreme quality ashless full synthetic two – cycle engine oil specially formulated from synthetic oils with advanced additives and fuel stabilizer to provide excellent clean-burning performance while protecting vital system parts . It withstands high heat and stress to protect against engine wear and harmful deposits under the higher operating temperatures typical of air-cooled services. Super Life 3500D-2T FS with Fuel Stabilizer helps to prevent fuel from deterioration, to purge and remove varnish and carbon deposits present in equipment.

#### APPLICATIONS:

***SUPER LIFE 3500D-2T FS*** is recommended for 2- cycle air-cooled engines use in power equipment of Europe, Japan, USA : CRAFTSMAN, HUSQVARNA, JOHN DEERE, RYOBI, MAKITA, HONDA, ECHO, RYAN, RED MAX, TORO, TANAKA, TMC, TROY BILT, LAWBOY, SHINDAIWA, STIHL, etc.

It meets and exceeds Engine Manufacturer’s warranty requirements for applications requiring:  
API TC      JASO FD      ISO - L – EGD      TISI

#### BENEFITS:

- Excellent engine protection, maintains strong capacity, prevents deposits on piston, spark-plug and in chimney pot. High reduction of exhaust smoke emissions.
- Provides exceptional lubricity and protection against piston scuffing, ring sticking and bearing wear, rust and corrosion.
- Helps engine running smoothly, freshly and strongly spurting out . Excellent fuel saving .
- Achieves maximum horsepower .
- Designed for both injection and premix lubrication up to a fuel/oil ratio of 50:1

#### TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	33.03
Specific Gravity @ 15°C (60°F)	ASTM D1298	0.860
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	40.26 7.85
Viscosity Index	ASTM D2270	170
Flash Point, °C (°F)	ASTM D92	74 (165)
Pour Point , °C (°F)	ASTM D97	-45 (-49)

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers



*Reference SDS No12020 database on our website at [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link*