



DURALIFE® TURBINE OILS

DURALIFE® TURBINE OILS are high quality turbine oil formulated from specially selected base oils with rust, foam and oxidation inhibitors and an anti-wear additive.

APPLICATIONS:

DURALIFE® TURBINE OILS are recommended for main lubrication of water, steam and gas turbines.

BENEFITS:

- Provide oxidation stability ,water separability, foam suppression.
- Provide high film strength to protect gears and bearings .
- Prolong gear tooth life through its effective anti-wear system.
- Protect against rust and corrosion.
- Superior demulsibility characteristics .

TYPICAL CHARACTERISTICS:

Test	Method	T 32	T 46	T 68	T100
API Gravity	ASTM D287	29.85	28.93	28.39	27.67
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.877	0.882	0.885	0.889
Viscosity @ 40°C, cSt	ASTM D445	32	46	68	100
Viscosity Index	ASTM D 2270	98	96	95	95
Flash Point, °C (°F)	ASTM D92	202 (396)	202 (396)	218 (424)	227 (441)
Pour Point, °C (°F)	ASTM D97	-12 (10)	-12 (10)	-9 (15.8)	-9 (15.8)
Color	ASTM D1500	1.0	1.5	2.0	2.0

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and bottle to collection centers

Reference SDS Number 12031 database on our website at www.amtecol.com OR scan the code for a direct link

