



## DURALIFE® GENERAL PURPOSE NON-ZINC R&O HYDRAULIC OILS

**DURALIFE® GENERAL PURPOSE NON-ZINC R&O HYDRAULIC OILS** are manufactured from high quality base oils with special additives to inhibit against rusting, oxidation and corrosion with good demulsibility characteristics.

### APPLICATIONS :

**DURALIFE® GENERAL PURPOSE NON-ZINC R&O HYDRAULIC OILS** are recommended for use in equipment where anti-wear performance is less critical and for equipment containing silver plated bearing surfaces where non-zinc oils are required.

### BENEFITS :

- Provide superior oxidation stability ,water separability, foam suppression.
- Protect against wear & scuffing in hydraulic pumps.
- Protect against rust and corrosion.
- Superior demulsibility characteristics.

### TYPICAL CHARACTERISTICS:

Test	Method	ISO 32	ISO 46	ISO 68	ISO100
API Gravity	ASTM D287	29.85	28.93	28.39	27.67
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.877	0.882	0.885	0.889
Viscosity @ 40°C, cSt	ASTM D445	32	46	68	100
Viscosity Index	ASTM D 2270	96	96	96	96
Flash Point, °C (°F)	ASTM D92	191 (376)	202 (396)	218 (424)	227 (441)
Pour Point, °C (°F)	ASTM D97	-30 (-22)	-30 (-22)	-20 (-4)	-20 (-4)
Color	ASTM D1500	1.0	1.5	2.0	2.0

*The above characteristics are average values based on recent production .Minor variations which do not affect product performance are to be expected in normal manufacture.*

### WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and bottle to collection centers

Reference SDS Number 12057 database on our website at [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link

